


Zubehör

Accessories



Verschluss-Schlitzschrauben, PA 6 GF30

Slotted screw plug, PA 6 GF30

Temperaturbereich -30°C ... +100°C

Temperature range -30°C ... +100°C

Gewinde / Thread
AH
mmDA
mm

St./Pcs.

EURO
100 St./Pcs.Bestellbez.
Order no.

IP 54


PG 7	6	10,0	15,0	100	8,00	BL/PA PG 7
PG 9	6	10,0	19,0	100	8,00	BL/PA PG 9
PG 11	6	10,0	22,0	100	9,00	BL/PA PG 11
PG 13,5	6	10,0	25,0	100	9,00	BL/PA PG 13,5
PG 16	6	10,0	27,0	100	9,50	BL/PA PG 16
PG 21	8	12,5	33,0	100	12,00	BL/PA PG 21
PG 29	8	13,0	44,5	100	27,00	BL/PA PG 29
PG 36	10	15,0	55,5	50	59,00	BL/PA PG 36
PG 42	10	15,5	62,5	50	72,00	BL/PA PG 42
PG 48	12	17,0	69,5	50	91,00	BL/PA PG 48

Farbe / Colour

lichtgrau / light grey, RAL 7035

Zubehör

Accessories



Sechskantmutter, PA 6 GF30

Hexagonal locknut, PA 6 GF30

Temperaturbereich -20°C ... +100°C

Temperature range -20°C ... +100°C

Gewinde / Thread
A

mm

H
mm

St./Pcs.

EURO
100 St./Pcs.Bestellbez.
Order no.

Polyamid PA 6 GF30 / Polyamide PA 6 GF30

PG 7	19	5	100	5,00	GM/PA 6k PG7	+ a
PG 9	22	5	100	5,50	GM/PA 6k PG9	+ a
PG 11	24	5	100	6,00	GM/PA 6k PG11	+ a
PG 13,5	27	6	100	6,50	GM/PA 6k PG13,5	+ a
PG 16	30	6	100	7,00	GM/PA 6k PG16	+ a
PG 21	36	7	100	11,00	GM/PA 6k PG21	+ a
PG 29	46	7	100	19,00	GM/PA 6k PG29	+ a
PG 36	60	8	50	43,00	GM/PA 6k PG36	+ a
PG 42	65	8	50	52,00	GM/PA 6k PG42	+ a
PG 48	70	8	50	62,00	GM/PA 6k PG48	+ a

Farben / Colours a

7035 = lichtgrau / light grey, RAL 7035 (Standard / standard)

9005 = schwarz / black, RAL 9005