




U-V(ZN)H n*4 Fasern (2,1mm) + B11Y PUR

Dielectric Armoured Cable 4-Fiber Subgroups Windmilling



Cable description

- 01. Central Element (GRP)
- 02. Tight Buffer Cable (0.9 mm)
- 03. Aramid
- 04. Individual Jacket (Ø2.1 mm)
- 05. Dielectric Armour
- 06. Outer Jacket

Applications

Direct connection to terminal equipments

Rodent protection

Rodent resistant

Options

Jackets: LSZH / PVC / PE / PA
 Special colour code
 Buffer Easy-Strip

Advantages

Compact / Resilient / Tough / Excellent mechanical resistance / Easy to strip (gel free) / Totally dielectric / Direct connectorization / Rodent protected.



All technical specifications are subject to change without prior notice. Consult WEYDEMEYER for the latest edition.

	SPECIFICATIONS	
Fibres	36	48
Subcables strength members	Aramid Yarns	
Ø Subcables (mm)	2.1	
Subcables jacket	Thermoplastic	
Colour	Orange (MM62) / Blue (MM50) / Yellow (SM)	
Identification	Numbers	
Armour	Fiberglass Braid	
Outer jacket	Polyurethane	
Weight (Kg/Km)	500	425
Outer Ø (mm)	23.7 ± 0.5	23.7 ± 0.5
Tensile Load Perm / Inst (N)	3000 / 4000	
Crush (N/100mm)	2000	
Temperature Range	-20°C to +70°C	
Min. Bending Radius (mm)	20 x Outer Ø	
Maximum Length	850 m	

Standards

Environmental and mechanical tests according to EN187000 and IEC60794.